

**50 µm PP-Film black opaque
with electrostatic charge.**

FOLIOCONTACT

Blackboard-Film

Rawmaterial:	PP coex/Cast 3-layers
Colour:	black matte
Surfacetreatment:	none
Ghauge:	50µ
Operating Temperature:	10° bis 45°C
Opacity:	100%
Printingprocess:	n. a.
Sheetsize:	600 x 800mm
Sheets per Roll	25
Roll length:	20m
SQM/ Roll:	12m²
Single-shipping	min 1 Roll
Packaging Units:	1, 2, 9, 18
1 Roll per	Dispenser
Shipping large amounts	Euro-Pallet
Storage Duration:	min. 5 Years (dry)



FOLIOCONTACT BLACKBOARD

is an environmental friendly Flip-Chart Media, made of Polypropylen.
It has been developed and been produced by NOPAR INTERNATIONAL GMBH.

FOLIOCONTACT is a special produced 3-layer coex cast PP-Film. The mid Layer is able to take on ionisation and keep it for at least 5 Years, depending on the storage conditions, packed and boxed at 40-50% rel. humidity, at 18°-22°C.

The 25 sheets in the size of 600mm width and 800mm length can easily be separated from the roll at the provided perforation line. Each sheet adhere to virtually any surface without any other tools, such as adhesive or pins disputes.

The film is ideally suited for use with non-permanent Window Markers, or Chalk. When using permanent markers, it will be not possible to clean the film surface again, except when alcoholic cleaning solution is taken (please care about dangerous Goods Regulations). FOLIOCONTACT BLACKBOARD is not made for printing or individual printed artworks in this case we recommend the product FOLIO CONTACT GRIDDED.

For further details please contact NOPAR INTERNATIONAL INC.

FOLIO CONTACT can be recycled, can be disposed with the yellow bag and capable for energy recovery. Safety data sheets can be requested if necessary.

Any reproduction or use of this publication or partially reproduced information in electronic or printed form is prohibited without written permission and acknowledgment by the owner.

Datasheet Release February 2024

NOPAR INTERNATIONAL

NOPAR International
Dortmunder Str. 32
28199 Bremen/Germany
Phone: +49 421 5208146 0
Fax: +49 421 5208146 9
Mail: info@nopar-international.com
Web: <http://www.nopar-international.com>



■ ■ ■ made in Germany

Please note that all information supplied is correct to date of print, information. It can change without prior notification. This information does not release the manufacturer from his obligation with regard to proper application and handling of the product. All content is based on available technical knowledge at the time of publication.